

Catalogue

Product Select

Product Type:

Search Compressor:

Application:

Refrigerant:

Voltage:

Frequency:

Compressor Cooling:

Green Cooling:

Unit settings

kCal/h, W | °C | Kg | cm

BTU/h | °F | lbs | in

Working conditions

Standard

Particular

Standard Conditions

	CECOMAF		ASHRAE		HCB CECOMAF		HCB ASHRAE	
	LBP LMBP	HMBP HBP	LBP LMBP	HMBP HBP	MBP VMBP	VMBP HMBP	MBP VMBP	VMBP HMBP
Evaporating temp. (°C)	-25	5	-23.3	7.2	-10	25	-10	25
Condensing temp. (°C)	55	55	55	55	55	70	55	70
Liquid temp. (°C)	55	55	32	46	55	70	46	61
Suction temp. (°C)	32	32	32	35	32	32	35	35
Ambient temp. (°C)	32	32	32	35	32	32	35	35

1 compressor found

Model	Displacement (cm³)	Refrigerant	Application	Compressor Cooling	Voltage/Frequency	Frequency (Hz)	Motor Type	ASHRAE (*)		CECOMAF (*)		Technical Data Sheet (*)
								Cooling (kCal/h)	COP (W/W)	Cooling (W)	COP (W/W)	
GL80AAa	8,10	R134a	LBP	S	220-240V 50Hz -1	50	RSIR	170	1,15	144	0,89	GL80AAa

(*) Under standard conditions

(**) Version 3

Navigate

[About Us](#)
[Products](#)
[Catalogue](#)
[Technical Information](#)
[News](#)
[Distribution Network](#)
[Customer Area](#)
[Contact](#)

[Legal notice](#)
[Cookies](#)
[Site Map](#)

Social

- [LinkedIn](#)
- [Our Blog](#)

Get in Touch

Mall Us
info@huayicompressor.es
Call
 +34 93 710 60 08
Address
 Antoni Forrellad, 2 - 08192
 Sant Quirze del Vallés
 Barcelona - Spain
The Group

CHANGHONG 长虹

华意压缩